



FLUORESCENT LIGHT

SPECIFICATION

- 1: POWER: 220V/50HZ/0.23KW
- 2: OUT SIDE SIZE: 1300Wx750Dx1850Hmm
- 3: INNER SIZE: 1220Wx660Dx660Hmm
- 4: WIND SPEED: 0.45 ± 0.2 M/S
- 5: CLEANLINESS: CLASS10 (ISO4)
- 6: NOISE RANGE: 58-62dB

No.	DESCRIPTION	QTY	MATERIAL
1	PREFILTER	1	G4
2	ELECTRICAL PANEL	1	
3	FANNER(EBM-R4E310-AP)	1	0.12 KW
4	CASING	1	SPCC T=1.1
5	FOAM	1	
6	CONTROL PANEL	1	
7	ULPA FILTER	1	U15(99.9995%@0.3um)
8	FLUORESCENT LIGHT	2	20W
9	PLEXIGIASS	1	T=4
10	TEMPERED GLASS	2	T=4
11	SOCKET	1	
12	WORK TOP	1	SUS304 T=1.1
13	STAND(CAN DISASSEMBLY)	1	SPCC T=1.1
14	STAND BACK PLATE	1	SPCC T=1.1
15	FOOT CUP	4	M12*150
16	CASTER	4	Heavy rotary wheel



StatiTech Ltd.

CLIENT	PROJECT	DES'D	ChlongLong Zhang	DATE	2009.02.25
		CHE'D		QTY	1:25
TITLE	DWG No.	APP'R		MAT'L	
		EDITION	A1	SCALE	1:25